



SOBY.COM
TRUSTED SINCE 1961



SØBY SS102-127-152 Grain augers

SØBY grain augers are an internationally renowned quality product that can be incorporated wherever grain and ground bulk products need to be conveyed. Conveying systems with SØBY grain augers can always be extended or adapted as and when needs change.



SØBY grain augers

Hot-dip galvanised and with double bearings at top shaft.

Basic machine

SØBY grain augers consist of:

- Motor bracket and auger head with outlet
- Extension sections 1-2-2.5-3-4 and 6 m with sleeve joints
- Auger foot with protective grating
- Motor
- V-belt drive complete or worm gear

Scope of application

SØBY grain augers have a wide range of applications in agriculture and the animal feed industry for conveying grain and ground bulk material. Grain augers can operate at all angles.

Accessories:

- Fig. 1: Auger foot / head with bearing and axle. (Ø150, OK160, Ø200)
- Fig. 2: Long inlet with slide, can be fitted with hopper, double inlet or under silo
- Fig. 3: Double inlet OK160, fits long inlet
- Fig. 4: Hopper with grate, fits long inlet
- Fig. 5: Inlet regulation for auger foot with protective grating
- Fig. 6: Bottom bearing with axle and bearing cover
- Fig. 7: Hanger

Fig 1.



Fig 2.




Fig 3.



Fig 4.




Fig 5.




Fig 6.



Fig 7.



SOBY TRUSTED
SINCE 1961

Viborgvej 306 · DK-7840 Højslev
(+45) 97 53 50 33 · soby@soby.com
www.soby.com